

#### **Chief Executive Officer**

Eric S. Gordon

#### **Board of Education**

Anne E. Bingham *Board Chair* 

Robert M. Heard Sr. Vice Chair

Louise P. Dempsey, Esq. Sara Elaqad, J.D. Denise W. Link Nigamanth Sridhar, Ph.D. Lisa Thomas, Ph.D. Kathleen C. Valdez, Esq.

### **Ex Officio Members**

Alex Johnson, Ph.D. Laura Bloomberg, Ph.D. To: All Service Providers

From: M. Angela Foraker, Executive Director Strategy, Sourcing, & Support

Date: November 4, 2022

Re: Addendum #1 for ITB 21368 – MetroHealth Clinic Upgrades at Clara Westropp, Mound, and Glenville

This Addendum shall hereby be and become a part of the Contract Documents the same as if originally bound thereto.

Each proposer shall acknowledge receipt of the Addendum in your proposal response. Failing to acknowledge this Addendum on the Addendum Acknowledgement Form may cause the response to be rejected.

This Addendum #1 reflects the following:

- Walkthrough Date
- Bid Due Date Extension
- Responses to Questions

Walkthrough Date: November 9, 2022 at 2:00 PM

Starting at Glenville High School, 650 E. 113<sup>th</sup> Street, Cleveland, Ohio 44108

Followed by Mound School, 5935 Ackley Rd. Cleveland, Ohio 44105

Finishing at Clara Westropp School, 19101 Puritas Avenue, Cleveland, Ohio 44135

## Extending ITB Due Date:

ORIGINAL ITB due date: November 9, 2022 at 1:00 PM (EST)

REVISED ITB due date: November 16, 2022 at 1:00 PM (EST)

**<u>REMINDER</u>**: Mailing of ITB responses are encouraged. However, hand deliveries will only be accepted from: **12:00 PM to 1:00 PM** on November 16, 2022. 1. Is this project prevailing wage?

Yes

2. Is there another completion date other than April 1, 2023?

Yes, May 26, 2023.

3. Hours of operations?

Clara Westropp7:35 am - 2:05 pmGlenville8:00 am - 3:05 pmMound8:35 am - 3:05 pmThe custodians are required to be onsite during construction. Therefore, contractors are required to report work hours at the start of the job.

4. What is the floor to deck height at each school?

Glenville 12'0" with a 3.5" concrete slab Mound 13'4" with a concrete slab on metal decking on bar joists Clara Westropp 11'4: with a concrete slab on metal decking on bar joists

5. Which buildings are sprinklered?

Glenville – No Mound – Yes Clara Westropp - No

6. Can one superintendent manage all three school projects?

Yes

7. Which schools have basements?

Glenville – Yes Mound – No Clara Westropp - Partial 8. Can deliveries be received at the school when the contractor is not on site?

All deliveries should be coordinated with the custodian. However, we do not encourage deliveries to the school without the contractor on site.

9. Are workers required to provide an FBI and BCI background checks?

Yes, both are required. This can be done at the CMSD East Professional Center located at 1349 E. 79<sup>th</sup> St., Cleveland, OH. Hours of operations will be listed within a link that will be provided to the successful bidder. Please provide a cashier's check, money order or debit card for \$47.25. The results will be available 30 days from filing. The phone number for Safety & Security is 216/838-0467, if you have any questions.

10. On the equipment/furniture plan (A4.0), elevation marker A4/A5.0 is used at the Check In Work Area. That elevation is labeled Staff Break Room and the layout/elevation do not match. What are the casework requirements for this room(Clara Westropp)?

See Sheets A4.0 and A5.0 for Revisions

11. Where is elevation B1/A5.0 used(Clara Westropp)?

See Sheets A4.0 and A5.0 for Revisions

12. Elevation A3 for Triage/Intake does not match the floor plan layout. What are the casework requirements for this room(Clara Westropp)?

See Sheets A4.0 and A5.0 for Revisions

13. Elevation A1/A5.0 does not match the floor plan. The floor plan shows 4 base and 4 wall cabinets, the elevation shows 2 base and 1 wall cabinet. Which is correct(Clara Westropp)?

See Sheets A4.0 and A5.0 for Revisions

14. The layout for Intake Triage (2/A4.0) and the elevations (C1 & A4/A5.0) do not match. What are the casework requirements for this room(Mound)?

See Sheets A4.0 and A5.0 for Revisions

15. In Check-In 101, the floor plan shows what appears to be a tall cabinet with one base & one wall cabinet next to it. The elevation (A1/A5.0) shows two base and one wall cabinet. Which is correct(Glenville HS)?

See Sheets A4.0 and A5.0 for Revisions, two base and one wall cabinets

16. Is any casework required in Staff Workroom 111? If so, please provide an elevation(Glenville HS).

No, only counters per detail on sheet A5.0

17. Can we visit the site?

Yes, November 9, 2022

18. Will the furniture be provided by others?

See notes

19. What is the hexagon symbol on proposed floor plan drawing(Clara Westropp)?

See Sheet A2.0 for notes

20. Glenville HS - Drawing A1.0 Exis/Demo Ceiling Plan - What are notes 6 and 7 indicate?

See Sheet A1.0 for notes

21. If countertops are screwed it is easy to remove. If it is glued it sometimes cannot be salvaged. Will it be considered a CO if we have to replace countertop?

Architect will decide at time of demo

# **DEMOLITION GENERAL NOTES:**

1. SEE FLOOR PLAN GENERAL NOTES ON SHEET A1.1 FOR DESCRIPTION OF REFERENCE "ORTHO LINE".

2. DEMOLITION PLAN SHOWS APPROXIMATE LAYOUT OF EXISTING BUILDING AND IS NOT INTENDED TO REPRESENT "AS-BUILT" CONDITIONS. CONTRACTOR SHALL VISIT THE SITE AND OTHERWISE BECOME FAMILIAR WITH ACTUAL CONDITIONS WHEN BIDDING THE WORK. PRIOR TO STARTING OF WORK, CONTRACTOR SHALL VERIFY EXISTING CONDITIONS, DIMENSIONS AND SIZES, ETC. OR ITEMS NOT INDICATED ON DRAWINGS, THAT MAY REQUIRE DEMOLITION BUT NOT DESCRIBED OR SHOWN.

3. EXISTING FIRE ALARM OR SPRINKLER MONITORING SYSTEM: MAINTAIN EXISTING SYSTEM IN SERVICE UNTIL NEW SYSTEM IS ACCEPTED. DISABLE SYSTEM ONLY TO MAKE SWITCHOVERS AND CONNECTIONS. NOTIFY AND OBTAIN PERMISSION FROM LANDLORD AND LOCAL FIRE SERVICE IN ADVANCE IN ACCORDANCE WITH AHJ REQUIREMENTS BEFORE PARTIALLY OR COMPLETELY DISABLING SYSTEM. MINIMIZE OUTAGE DURATION. MAKE TEMPORARY CONNECTIONS TO MAINTAIN SERVICE IN AREA ADJACENT TO WORK AREA.

4. PRIOR TO ANY DEMOLITION WORK, CONTRACTOR MUST FIELD VERIFY ALL EXISTING MECHANICAL, PLUMBING AND ELECTRICAL WORK LOCATED IN THE TENANT SPACE.

5. WALLS, PARTITIONS, DOORS, FRAMES, AND OTHER ITEMS TO BE REMOVED ARE SHOWN DASHED. SERVICES WITHIN WALLS AND PARTITIONS SHALL ALSO BE REMOVED. REPAIR AND PATCH EXISTING WALLS SHOWN TO REMAIN WHERE INTERSECTING WALLS, DOORS, FRAMES, ETC. ARE SHOWN TO BE REMOVED AND WHERE EXISTING CONSTRUCTION WILL NOW BE EXPOSED IN THE NEW CONSTRUCTION.

6. EXISTING CONSTRUCTION SHOWN TO REMAIN SHALL BE PROTECTED DURING DEMOLITION. DAMAGE TO EXISTING CONSTRUCTION SHOWN TO REMAIN SHALL BE RESTORED TO MATCH PRE-DAMAGED CONDITION. ALL DAMAGED EXISTING STRUCTURAL FIREPROOFING MATERIAL IS TO BE PATCHED/REPAIRED AS REQUIRED.

7. REMOVE ALL EXISTING OBSOLETE MISCELLANEOUS NON-LOADBEARING ITEMS IN THEIR ENTIRETY THROUGHOUT TENANT SPACE, PARTICULARLY WHERE EXISTING ITEMS WILL INTERFERE WITH THE INSTALLATION OF NEW CONSTRUCTION, OR WHERE EXISTING ITEMS WILL BE EXPOSED IN THE NEW CONSTRUCTION, UNLESS SPECIFICALLY SHOWN ELSEWHERE IN THE CONTRACT DOCUMENTS TO REMAIN. REPAIR AND PATCH ALL SURFACES TO REMAIN, WITH MATERIALS MATCHING EXISTING CONSTRUCTION. COORDINATE WITH NEW CONSTRUCTION.

8. REMOVE ALL EXISTING OBSOLETE PLUMBING, MECHANICAL, AND ELECTRICAL EQUIPMENT IN THEIR ENTIRETY THROUGHOUT TENANT SPACE PARTICULARLY WHERE EXISTING ITEMS WILL INTERFERE WITH THE INSTALLATION OF NEW CONSTRUCTION, OR WHERE EXISTING ITEMS WILL BE EXPOSED IN THE NEW CONSTRUCTION, UNLESS SPECIFICALLY SHOWN ELSEWHERE IN THE CONTRACT DOCUMENTS TO REMAIN. COORDINATE WITH NEW CONSTRUCTION.

9. IN ALL AREAS WHERE DEMOLITION CAUSES UNEVENNESS AND/OR VOIDS IN THE FLOORS, THE CONTRACTOR SHALL BE RESPONSIBLE FOR PATCHING AND FLOOR LEVELING TO LEVEL FLOOR WITH ADJACENT SURFACES. FLOOR LEVELING MATERIAL SHALL BE COMPATIBLE WITH NEW FLOOR FINISH MATERIALS.

10. IN ALL AREAS WHERE DEMOLITION CAUSES UNEVENNESS AND/OR VOIDS IN GYPSUM BOARD WALLS, THE CONTRACTOR SHALL BE RESPONSIBLE FOR PATCHING AND LEVELING THE THE WALL WITH ADJACENT SURFACES. APPLY A SKIM COATING TO WALL SURFACES WITH EXTENSIVE VOIDS AND/OR UNEVENNESS.

11. ALL BUILDING SERVICES REQUIRED TO MAINTAIN BUILDING OPERATION OF OTHER AREAS SHALL BE MAINTAINED. BUILDING SERVICES IN FINISHED SPACES SHALL BE CONCEALED, UNLESS OTHERWISE INDICATED. BUILDING SERVICES ENCOUNTERED IN DEMOLISHED PARTITIONS AND CEILINGS WHICH ARE TO REMAIN SHALL BE REROUTED AND CONCEALED. THOSE BUILDING SERVICES THAT ARE INDICATED TO BE ABANDONED SHALL BE CAPPED AND CONCEALED IN THE FLOOR, WALL OR CEILING. CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY ALL SERVICES PRIOR TO REMOVAL AND DISCONNECTION INCLUDING ELECTRICAL, HVAC, PLUMBING, SECURITY, AND TELEPHONE/DATA FOR ADJOINING OCCUPIED SPACES.

12. ALL EXISTING CONCRETE FLOORS SHALL BE PREPARED TO RECEIVE NEW FLOOR FINISHES. THIS SHALL CONSIST OF BUT NOT LIMITED TO SCRAPING, GRINDING, APPLYING FLOOR LEVELING MATERIAL, ETC.

## WALL LEGEND

EXIST. WALLS

C===== WALLS AND MILLWORK TO BE REMOVED

## PLAN CODED NOTES:

REMOVE PORTION OF EXIST. INTERIOR MSY. WALLS TO CREATE A NEW OPNG.;

INDICATED BY


-CHALK/MARKER BOARDS


- PROVIDE STL. LINTELS AT EACH OPEN; SEE LINTEL SCHEDULE FOR SIZE
- REMOVE EXIST. DOORS AND MTL. FRAME REMOVE EXIST. THROUGH WALL A.C. / VENTILATOR
- 4. REMOVE

-FLOORING


- -WALL BASE -ACCESSORIES (CLOCKS, -ACOUST. CLG. TILES ETC. MIRRORS, FIRE EXTINGUISHERS -ADHESIVE -A/V TECH. EQUIPMENT CMSD SHALL REMOVE ALL FURNISHINGS, DEHUMIDIFIERS, WALL MNTD. POSTERS.
- REMOVE ALL EXIST. CEILING TILES REMOVE ALL SURFACE MOUNTED LIGHTING FIXTURES


\*SALVAGE ALL ACCESSORIES AND TECH. EQUIP.; CONTRACTOR TO REMOVE AND CMSD SHALL STORE


































X'-X" A.F.F. INDICATES CEILING HEIGHT

## **GENERAL NOTES:**

- I ALL WORK, ITEMS AND MATERIALS ARE **NEW** UNLESS PRECEDED BY THE WORD "EXISTING".
- II PATCHING- ALL EXISTING SURFACES DISTURBED BY RENOVATIONS. WALLS SHALL BE PATCHED TO MATCH EXIST. THEN APPLY NEW FINISHES.
- III SOUND- ALL PARTITIONS SHALL INCLUDE SOUND ATTENUATION BATTS AND EXTEND TO UNDERSIDE OF STRUCTURE. IV FURNISHINGS- BY OWNER.
- V EQUIP-PER PLAN.
- VI COMPUTERS- PER PLAN.
- VII TELEPHONES/DATA- PER OWNER VIII CEILINGS- NEW THROUGHOUT; PATCH, SEAL, CLOSE AND RELOCATE ITEMS AS REQUIRED.
- IX WALLS- PAINT.
- X FLOORS- NEW. XI POWER- AS REQUIRED BY PLAN.
- XII THE METHOD OF ATTACHMENT FOR ALL ITEMS THAT ARE TO BE
- SUSPENDED ARE TO BE SUSPENDED FROM THE FLR. STRUCT. ABOVE. XIV REFERENCE FINISH FLOOR AT 0'-0".
- XV REFER TO AX.X FOR PARTITION TYPES. XVI REFER TO AX.X FOR DOOR SCHEDULE.
- XVII THESE DRAWINGS HAVE BEEN COORDINATED WITH EXISTING CONDITIONS AS THEY ARE BELIEVED TO EXIST. THE CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND NOTIFY THE ARCHITECT/OWNER, IN A TIMELY MANNER, REGARDING ANY AND ALL DISCREPANCIES BETWEEN THE CONTRACT DOCUMENTS AND ACTUAL CONDITIONS.
- XVIII REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR ADDITIONAL WORK.
- XIX UPON COMPLETE REMOVAL OF EXIST. FLRNG. ARCHITECT AND OWNER TO PERFORM DETAIL REVIEW AND INSPECTION OF EXIST. SUBFLOOR XX NEW WALLS SHALL BE INSTALLED WITH THE INTENT OF PROVIDING ACCESS TO ALL EXIST. OUTLETS AND DEVICES IDENTIFIED AS EXIST. TO
- REMAIN. XXI REFER TO INTERIOR DRAWINGS FOR CASEWORK INFORMATION AND DIMENSIONS

## **TYPICAL NOTES**

1. ALL WORK SHALL COMPLY WITH ALL APPLICABLE LOCAL AND STATE BUILDING CODES, FIRE SAFETY CODES AND REGULATIONS INCLUDING, BUT NOT LIMITED TO, THE OHIO BUILDING CODE (OBC) AND THE AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES (ADAAG). ANY CONFLICTS BETWEEN THE WORK INDICATED WITHIN THESE DOCUMENTS AND SAID CODES OR REGULATIONS NOTED BY THE CONTRACTOR SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT PRIOR TO PROCEEDING WITH THE WORK.

2. MAKE ARRANGEMENTS 72 HOURS MINIMUM IN ADVANCE WITH THE OWNER FOR ANY INTERRUPTIONS OF UTILITY SERVICE.

3. EACH CONTRACTOR AND VENDOR SHALL VISIT THE SITE AND BECOME FAMILIAR WITH ALL CONDITIONS AND CLEARANCES PRIOR TO SUBMITTING A PROPOSAL.

4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING AND PAYING FOR ALL PERMITS AND INSPECTIONS AS REQUIRED.

5. SHOULD ANY OF THE DETAILED INSTRUCTIONS ON THE DRAWINGS CONFLICT WITH THE NOTES OR SPECIFICATIONS OR WITH EACH OTHER, THE STRICTEST PROVISION SHALL APPLY. ANY SUCH CONFLICT SHALL BE REPORTED TO THE ARCHITECT.

6. ALL SECTIONS AND DETAILS SHALL BE CONSIDERED TYPICAL AND APPLY FOR THE SAME AND SIMILAR SITUATIONS THROUGHOUT THE STRUCTURE UNLESS SPECIFICALLY NOTED OTHERWISE.

7. THE CONTRACTOR SHALL VERIFY ALL RELEVANT DIMENSIONS, ELEVATIONS ANGLES AND EXISTING CONDITIONS BEFORE PROCEEDING WITH THE AFFECTED WORK AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES IMMEDIATELY.

8. INSTALL ALL MATERIALS AND EQUIPMENT IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.

9. ALL LOOSE DEBRIS/TRASH SHALL BE DEPOSITED IN A COVERED TRASH RECEPTACLE OR REMOVED FROM THE SITE. NO LOOSE DEBRIS/TRASH SHALL BE LEFT ON ROOFS, SPACES OPEN TO AIRPORT OPERATIONS AREA (AOA), NEAR CONVEYANCE SYSTEMS, OR IN ANY OPEN TRASH CONTAINERS

10. ALL CONTRACTORS AND SUBCONTRACTORS FOR THE WORK OF THIS CONTRACT SHALL BE PROPERLY LICENSED AND REGISTERED IN ACCORDANCE WITH THE REGULATIONS OF CLEVELAND, OHIO.


11. AT ALL TIMES WHEN WORK IS IN PROGRESS, A REPRESENTATIVE OF THE CONTRACTOR OR SUB-CONTRACTOR SHALL BE ON SITE AND AUTHORIZED TO ANSWER QUESTIONS OR RECEIVE INSTRUCTIONS FROM THE OWNER OR ARCHITECT.


12. ALL UNUSED/ABANDONED FLOOR/WALL OPENINGS SHALL BE SEALED OR FIRE STOPPED.

13. DUE TO HEALTH RELATED REASONS, USE OF CHINESE-MADE GYPSUM WALLBOARD IS NOT PERMITTED TO BE USED ON THE PROJECT.

14. ALL "LOUD" WORK (CUTTING, CORING, SAWING, ETC.) WILL BE CONDUCTED AT NIGHT WHEN THE CONCOURSE IS NOT OCCUPIED BY PASSENGERS (AFTER 10PM, BEFORE 5AM)

15. PROVIDE LOCKS AT ALL CABINETRY DOORS AND DRAWERS








## GENERAL NOTES


- B. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO CROSS-CHECK THE INTERIOR DRAWINGS WITH THE ARCHITECTURAL DRAWINGS PRIOR TO THE ORDERING / INSTALLATION OF CASEWORK. ANY DISCREPANCIES BETWEEN THE ARCHITECTURAL AND INTERIOR DRAWINGS SHALL BE BROUGHT TO THE C. COORDINATE THE INSTALLATION WITH OTHER TRADES AS REQUIRED TO ENSURE A NEAT AND ORDERLY INSTALLATION. NOTIFY ARCHITECT/ENGINEER OF ANY DISCREPANCIES BEFORE STARTING WORK. DOCUMENTS. INFORMATION REGARDING THE COMPLETE WORK IS DISPERSED THROUGHOUT THE DOCUMENT SET AND CANNOT BE ACCURATELY DETERMINED WITHOUT REFERENCE TO THE COMPLETE EXPENSIVE LABOR, MATERIALS AND EQUIPMENT SHALL BE ASSUMED TO BE REQUIRED AND SHALL BE F. WHEN WORK, NOT SPECIFICALLY CALLED OUT, IS REQUIRED TO COMPLETE THE PROJECT, IT SHALL BE G. THE PROPER RECEIPT AND UNLOADING OF ALL NEW MATERIALS AND EQUIPMENT AT THE JOBSITE IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR. SECURE AND SAFE STORAGE OF ALL MATERIALS AND EQUIPMENT WILL BE PROVIDED BY THE GENERAL CONTRACTOR, GENERAL CONTRACTOR SHALL
- ADVISE ARCHITECT & OWNER OF ALL DAMAGED, DEFICIENT OR OVERSHIPMENTS OF OWNER SUPPLIED MATERIALS. GENERAL CONTRACTOR SHALL COMPLETE AND SUBMIT ALL NECESSARY PAPERWORK AND ARRANGE INSPECTIONS OF DAMAGED GOODS AND RETURN AS PER CONSTRUCTION REQUIREMENTS. I. ENSURE THAT ALL SURFACES TO RECEIVE FINISHES ARE CLEAN, TRUE AND FREE OF IRREGULARITIES.
- J. REFER TO ELEVATIONS FOR FINISHES THAT MAY NOT BE NOTED ON THE FINISH PLAN. TRANSITION IN FLOORING SHALL BE LOCATED AT CENTER OF DOOR OR OPENING UNLESS NOTED OTHERWISE (U.N.O.).
- M. DO NOT INSTALL FLOORING MATERIALS OVER EXPANSION JOINTS. PROVIDE EXPANSION JOINT COVERS. N. SEE FINISH SCHEDULE, INTERIOR ELEVATIONS AND REFLECTED CEILING PLANS FOR ADDITIONAL FINISH


- T. SEE TYPICAL MOUNTING HEIGHTS ON SHEET I-201. VERIFY MOUNTING HEIGHTS SHOWN FOR TOILET ACCESSORIES WILL ALLOW FOR FULL OPERATION OF UNITS. NOTIFY ARCHITECT OF ANY POSSIBLE
- OTHERWISE DIRECTED BY OWNER. COORDINATE MASTER KEYING AND OVERALL KEYING SCHEDULE
- X. WALL CABINETS 24" HIGH SHALL HAVE ONE ADJUSTABLE SHELF. WALL CABINETS 25"-36" HIGH SHALL

- BB. INSTALL FILLER PANELS WHERE REQUIRED. PROVIDE AT WALL JUNCTION TO ALLOW DOORS TO OPEN COMPLETELY (MINIMUM 100 DEGREES). FILLERS SHALL EXTEND THE FULL DEPTH OF CABINET TO CREATE A FLUSH SURFACE ON TOP AND/OR BOTTOM OF CASE. FILLER FINISH SHALL MATCH ADJACENT
- CC. BASE AND TALL CABINETS SHALL BE 24" DEEP U.N.O. WALL CABINETS SHALL BE 14"-15" DEEP U.N.O. DD. INSTALL HEAVY-DUTY WORKSURFACE SUPPORT BRACKETS AS REQUIRED TO FULLY SUPPORT WORKSURFACE. BRACKETS SHALL BE METAL WITH WIREWAY OPENING (A&M HYBRID BRACKETS OR
- EE. INSTALL GROMMETS IN WORKSURFACES FOR ACCESS TO ELECTRIC AND DATA OUTLETS. COLOR TO BE FF. ALL FURNITURE AND EQUIPMENT SHALL BE OWNER PROVIDED U.N.O. SHOWN IN PLAN FOR REFERENCE.



SV-1	SV-2





## GENERAL NOTES

- A. DO NOT SCALE DRAWINGS. B. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO CROSS-CHECK THE INTERIOR DRAWINGS WITH THE ARCHITECTURAL DRAWINGS PRIOR TO THE ORDERING / INSTALLATION OF CASEWORK. ANY DISCREPANCIES BETWEEN THE ARCHITECTURAL AND INTERIOR DRAWINGS SHALL BE BROUGHT TO THE ARCHITECTS ATTENTION FOR IMMEDIATE CLARIFICATION. C. COORDINATE THE INSTALLATION WITH OTHER TRADES AS REQUIRED TO ENSURE A NEAT AND ORDERLY INSTALLATION. NOTIFY ARCHITECT/ENGINEER OF ANY DISCREPANCIES BEFORE STARTING WORK. D. GENERAL CONTRACTOR AND SUB-CONTRACTORS SHALL CAREFULLY REVIEW THE CONSTRUCTION DOCUMENTS. INFORMATION REGARDING THE COMPLETE WORK IS DISPERSED THROUGHOUT THE DOCUMENT SET AND CANNOT BE ACCURATELY DETERMINED WITHOUT REFERENCE TO THE COMPLETE DOCUMENT SET. E. WHERE THERE MAY BE A CONFLICT IN THE SPECIFICATIONS AND/OR DRAWINGS, THEN THE MORE EXPENSIVE LABOR, MATERIALS AND EQUIPMENT SHALL BE ASSUMED TO BE REQUIRED AND SHALL BE PROVIDED BY THE GENERAL CONTRACTOR TO THE SATISFACTION OF THE TENANT. F. WHEN WORK, NOT SPECIFICALLY CALLED OUT, IS REQUIRED TO COMPLETE THE PROJECT, IT SHALL BE PROVIDED BY THE GENERAL CONTRACTOR WITH THE BEST MATERIALS AND WORKMANSHIP. G. THE PROPER RECEIPT AND UNLOADING OF ALL NEW MATERIALS AND EQUIPMENT AT THE JOBSITE IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR. SECURE AND SAFE STORAGE OF ALL MATERIALS
- AND EQUIPMENT WILL BE PROVIDED BY THE GENERAL CONTRACTOR. GENERAL CONTRACTOR SHALL ADVISE ARCHITECT & OWNER OF ALL DAMAGED, DEFICIENT OR OVERSHIPMENTS OF OWNER SUPPLIED MATERIALS. GENERAL CONTRACTOR SHALL COMPLETE AND SUBMIT ALL NECESSARY PAPERWORK AND ARRANGE INSPECTIONS OF DAMAGED GOODS AND RETURN AS PER CONSTRUCTION REQUIREMENTS. H. FINISHES SHALL BE SUBMITTED TO THE ARCHITECT FOR APPROVAL PRIOR TO ORDERING OR INSTALLATION, WHERE DIRECTED IN THE SPECIFICATIONS.
- I. ENSURE THAT ALL SURFACES TO RECEIVE FINISHES ARE CLEAN, TRUE AND FREE OF IRREGULARITIES. DO NOT PROCEED WITH WORK UNTIL UNSATISFACTORY CONDITIONS HAVE BEEN CORRECTED. J. REFER TO ELEVATIONS FOR FINISHES THAT MAY NOT BE NOTED ON THE FINISH PLAN. TRANSITION IN FLOORING SHALL BE LOCATED AT CENTER OF DOOR OR OPENING UNLESS NOTED OTHERWISE (U.N.O.). K. PATCH, SMOOTH AND OTHERWISE PREPARE FLOOR SLAB AS REQUIRED FOR INSTALLATION OF
- FLOORING MATERIALS. L. PROVIDE RESILIENT BASE IN ALL FINISHED FLOORING AREAS UNLESS SCHEDULED OTHERWISE. M. DO NOT INSTALL FLOORING MATERIALS OVER EXPANSION JOINTS. PROVIDE EXPANSION JOINT COVERS. N. SEE FINISH SCHEDULE, INTERIOR ELEVATIONS AND REFLECTED CEILING PLANS FOR ADDITIONAL FINISH
- INFORMATION. O. CORNER GUARDS TO BE PLACED ON ALL EXTERIOR GYPSUM BOARD CORNERS. REFER TO
- SPECIFICATION SECTION 10 26 00 FOR ADDITIONAL INFORMATION. P. PROVIDE TRANSITION AT ALL CHANGES IN FLOOR MATERIALS, UNO.
- Q. PATCH, SMOOTH AND OTHERWISE PREPARE FLOOR SLAB AS REQUIRED FOR INSTALLATION OF FLOORING MATERIALS. R. INSTALL A SOAP DISPENSER AND PAPER TOWEL DISPENSER AT EACH SINK.
- S. THE INTENT OF THESE ELEVATIONS IS TO SHOW LOCATIONS OF MAJOR INTERIOR ELEMENTS. ELEVATIONS MAY NOT SHOW ALL ITEMS IN ALL ROOMS. T. SEE TYPICAL MOUNTING HEIGHTS ON SHEET I-201. VERIFY MOUNTING HEIGHTS SHOWN FOR TOILET ACCESSORIES WILL ALLOW FOR FULL OPERATION OF UNITS. NOTIFY ARCHITECT OF ANY POSSIBLE
- DISCREPANCIES PRIOR TO INSTALLATION. U. SEE INTERIOR DETAILS FOR ADDITIONAL CASEWORK INFORMATION.
- V. CASEWORK SHALL HAVE A 4" BACKSPLASH AND/OR SIDESPLASH AND 4" TOE KICK UNLESS NOTED OTHERWISE (U.N.O.).
- W. ALL CASEWORK SHALL LOCK. LOCKS WITHIN A GIVEN ROOM SHALL BE KEYED ALIKE UNLESS OTHERWISE DIRECTED BY OWNER. COORDINATE MASTER KEYING AND OVERALL KEYING SCHEDULE WITH OWNER.
- X. WALL CABINETS 24" HIGH SHALL HAVE ONE ADJUSTABLE SHELF. WALL CABINETS 25"-36" HIGH SHALL HAVE TWO ADJUSTABLE SHELVES UNLESS INDICATED OTHERWISE ON ELEVATIONS.
- Y. BASE CABINETS SHALL HAVE ADJUSTABLE SHELVES AS INDICATED ON ELEVATIONS AND DETAILS (MINIMUM OF ONE SHELF).
- Z. CABINET SHELVING SHALL BE FULL DEPTH. DRAWER BOXES SHALL BE FULL HEIGHT. PROVIDE MAXIMUM DRAWER BOX DEPTH AVAILABLE. AA. INSTALL CHAIN STOPS IN ALL LOCATIONS WHERE CABINET DOOR IS ADJACENT TO A WALL OR OTHER
- OBSTRUCTION. BB. INSTALL FILLER PANELS WHERE REQUIRED. PROVIDE AT WALL JUNCTION TO ALLOW DOORS TO OPEN COMPLETELY (MINIMUM 100 DEGREES). FILLERS SHALL EXTEND THE FULL DEPTH OF CABINET TO CREATE A FLUSH SURFACE ON TOP AND/OR BOTTOM OF CASE. FILLER FINISH SHALL MATCH ADJACENT CASEWORK.
- CC. BASE AND TALL CABINETS SHALL BE 24" DEEP U.N.O. WALL CABINETS SHALL BE 14"-15" DEEP U.N.O. DD. INSTALL HEAVY-DUTY WORKSURFACE SUPPORT BRACKETS AS REQUIRED TO FULLY SUPPORT WORKSURFACE. BRACKETS SHALL BE METAL WITH WIREWAY OPENING (A&M HYBRID BRACKETS OR EQUAL). COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.
- EE. INSTALL GROMMETS IN WORKSURFACES FOR ACCESS TO ELECTRIC AND DATA OUTLETS. COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE. FF. ALL FURNITURE AND EQUIPMENT SHALL BE OWNER PROVIDED U.N.O. SHOWN IN PLAN FOR REFERENCE.

## LEGEND




SV-1 SV-2
-----------

PLAN KEYED NOTES:


INDICATED BY

## **ABBREVIATIONS**




KEY PLAN SCALE: NTS


CLEVELAND         NETROPOLITAN         SCHOOL DISTRICT					
Proiect 1	leam:				
<section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header>					
W. Daniel	W. DAN BICKERSTA 12608	FF, II	508		
PERMIT ISSUANCE		WDB, II	08.26.2022		
ISSUED		BY	DATE		
MOUND ELEMENTARY SCHOOL Interior Alteration New MetroHealth ODH SBHC Health Care Expansion Program					
5935 Ackley Road Cleveland, OH 44105					
MetroHealth         MEDICAL CENTER         2000 METROHEALTH DR.         2000 METROHEALTH DR.					
EQUIF			_		
Date: 08.26.2022			4.0		




ROOM FINISH SCHEDULE						
	FLOOR		WALL FINISH- selection by Owner			
	FINISH	BASE	NORTH	SOUTH	EAST	WEST
	SV-2	RB-1				
	SV-2	RB-1				
	SV-1	RB-1				
М	SV-2	RB-1				
	SV-2	RB-1				
	SV-2	RB-1				
1	SV-1	RB-1				
	SV-1	RB-1				
	SV-2	RB-1				
DS	SV-2	RB-1				
	SV-2	RB-2				
	SV-2	RB-1				




## WALL CABINET 12 32 16.W1 1" = 1'-0"



# SOLID SURFACE COUNTERTOP **DETAIL** 6" = 1'-0"



## ADA SINK BASE 12 32 16.B1A 1/2" = 1'-0"



## TYPICAL EXAM ROOM 1/4" = 1'-0"

## GENERAL NOTES

- A. ALL OUTSIDE CORNERS OF GYPSUM BOARD WALLS SHALL RECEIVE CORNER GUARDS. INSTALL CORNER GUARDS AT TOP OF BASE.
- B. PROVIDE TRANSITIONS AT ALL CHANGES IN FLOORING FINISH, UNO. C. FLOOR MATERIALS AND/OR COLOR CHANGES BETWEEN ROOMS OR SPACES SHALL TRANSITION AT CENTER OF DOOR OR OPENING UNLESS NOTED OTHERWISE (U.N.O.). D. ALL EXPOSED CONDUIT, DUCTWORK, ACCESS PANELS, STRUCTURAL STEEL, ETC. SHALL BE PAINTED TO MATCH WALL OR CEILING U.N.O.
- E. INTERIOR HOLLOW METAL WINDOW FRAMES SHALL BE PAINTED TO MATCH DOOR FRAMES U.N.O. F. FINISH SCHEDULE CALLS OUT PAINT COLOR ONLY. SEE SPECIFICATIONS FOR PAINT TYPE AND SHEEN. G. SEE INTERIOR PLANS FOR ADDITIONAL ACCENT PAINT COLORS AND LOCATIONS. H. SEE INTERIOR PLANS FOR FLOOR PATTERNS AND ACCENT PAINT LOCATIONS.
- I. SEE REFLECTED CEILING PLANS FOR SOFFIT PAINT COLORS. J. PAINT INTERIOR DOOR FRAMES AND HOLLOW METAL DOORS P-X U.N.O.
- K. DO NOT INSTALL FLOORING MATERIALS OVER EXPANSION JOINTS. PROVIDE EXPANSION JOINT COVERS. L. ALL CASEWORK SHALL LOCK. LOCKS WITHIN A GIVEN ROOM SHALL BE KEYED ALIKE UNLESS OTHERWISE DIRECTED BY OWNER. COORDINATE MASTER KEYING AND OVERALL KEYING SCHEDULE WITH OWNER.
- M. CASEWORK SHALL HAVE A 4" BACKSPLASH AND/OR SIDESPLASH AND 4" TOE KICK UNLESS NOTED OTHERWISE (U.N.O.). N. WALL CABINETS 24" HIGH SHALL HAVE ONE ADJUSTABLE SHELF. WALL CABINETS 25"-36" HIGH SHALL
- HAVE TWO ADJUSTABLE SHELVES UNLESS INDICATED OTHERWISE ON ELEVATIONS. O. BASE CABINETS SHALL HAVE ADJUSTABLE SHELVES AS INDICATED ON ELEVATIONS AND DETAILS
- (MINIMUM OF ONE SHELF). P. CABINET SHELVING SHALL BE FULL DEPTH. DRAWER BOXES SHALL BE FULL HEIGHT. PROVIDE
- MAXIMUM DRAWER BOX DEPTH AVAILABLE. Q. INSTALL CHAIN STOPS IN ALL LOCATIONS WHERE CABINET DOOR IS ADJACENT TO A WALL OR OTHER
- OBSTRUCTION. R. INSTALL FILLER PANELS WHERE REQUIRED. PROVIDE AT WALL JUNCTION TO ALLOW DOORS TO OPEN COMPLETELY (MINIMUM 100 DEGREES). FILLERS SHALL EXTEND THE FULL DEPTH OF CABINET TO CREATE A FLUSH SURFACE ON TOP AND/OR BOTTOM OF CASE. FILLER FINISH SHALL MATCH ADJACENT CASEWORK.
- S. BASE AND TALL CABINETS SHALL BE 24" DEEP U.N.O. WALL CABINETS SHALL BE 14"-15" DEEP U.N.O. T. INSTALL HEAVY-DUTY WORKSURFACE SUPPORT BRACKETS AS REQUIRED TO FULLY SUPPORT WORKSURFACE. BRACKETS SHALL BE METAL WITH WIREWAY OPENING (A&M HARDWARE HYBRID BRACKETS OR EQUAL). COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.
- U. INSTALL GROMMETS IN WORKSURFACES FOR ACCESS TO ELECTRIC AND DATA OUTLETS. COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE. V. INSTALL A SOAP DISPENSER AND PAPER TOWEL DISPENSER AT EACH SINK.
- W. THE INTENT OF THESE ELEVATIONS IS TO SHOW LOCATIONS OF MAJOR INTERIOR ELEMENTS. ELEVATIONS MAY NOT SHOW ALL ITEMS IN ALL ROOMS. X. ALL FURNITURE AND EQUIPMENT SHALL BE OWNER PROVIDED U.N.O.

## **REFERENCED KEYNOTES**

09 65 13.A	RESILIENT BASE
12 32 16.B1A	ACCESSIBLE SINK BASE
12 32 16.B3	DOOR/DRAWER BASE
12 32 16.B4	DRAWER BASE
12 32 16.F	FILLER PANEL
12 32 16.W1	WALL CABINET
12 36 61.16.A	SOLID SURFACE MATERIAL COUNTERTOP

06 40 23 INTERIOR ARCHITECTURAL WOODWORK


- 08 87 00 ARCHITECTURAL WINDOW FILMS
- 09 51 13 ACOUSTICAL PANEL CEILINGS 09 65 13 RESILIENT BASE AND ACCESSORIES
- 09 65 16 RESILIENT SHEET FLOORING 09 91 23 INTERIOR PAINTING
- 10 26 00WALL AND DOOR PROTECTION10 28 00TOILET, BATH, AND LAUNDRY ACCESSORIES
- 12 32 16 MANUFACTURED PLASTIC-LAMINATE CLAD CASEWORK 12 36 61.16 SOLID SURFACING COUNTERTOPS

## **ABBREVIATIONS**

- P PAINT PC POLISHED CONCRETE PL PLASTIC LAMINATE RB RESILIENT BASE SS SOLID SURFACE
- SV SHEET VINYL
- 10 28 00 TOILET ROOM ACCESSORIE CH-1 COAT HOOK
- GRAB BAR, 36" GRAB BAR, 42" GB-1 GB-2 GB-3
- GRAB BAR, 18" MIRROR 24"x60" PAPER TOWEL DISPENSER M-1
- SANITARY UNIT DISPOSAL SUD-1 TOILET TISSUE DISPENSER

## PLAN KEYNOTES

- 1/2 PLYWOOD SUBSTRATE 1/2" MILLWORK REVEAL, STAINLESS STEEL. MFG: FRY REGLET, OR EQUA
- 1/2" RADIUS 1/2" SOLID SURFACE COUNTER ON PLYWOOD SUBSTRATE 4" HIGH (U.N.O.) AND 1/2" THICK BACKSPLASH
- ADJUSTABLE SHELF
   BLOCKING AS REQUIRE
   CABLE TRAY CHASE
- CEILING. REFER TO REFLECTED CEILING PLAN FOR ADDITIONAL INFORMATION
- DRAWERS SIDES SHALL BE FULL HEIGHT WITH INTEGRAL FILE RAILS 11. DRAWERS SIDES SHALL BE FULL HEIGHT
- 12. GROMMET 13. METAL SUPPORT BRACKET. MFG: A&M HARDWARE, HYBRID WORKSTATION BRACKET OR EQUAL
- 14. PLAM ENCLOSURE ABOVE WALL CABINET. FACE OF ENCLOSURE SHALL BE FLUSH WITH FRONT AND SIDE OF WALL CABINET AND EXTEND TO UNDERSIDE OF CEILING. PLAM ON 3/4" PLYWOOD, FASTENED TO STUD FRAME WITH CONCEALED FASTENERS
- 15. PROVIDE PROTECTION AT KNEE CLEARANCE, SINK SHALL NOT BE EXPOSED 16. PROVIDE STRUCTURAL SUPPORT AS REQUIRED
- 17. REMOVABLE ACCESS PANEL 18. RESILIENT BASE
- 19. TACKBOARD 20. WORKSURFACE
- 21. FOR WALL FINISH, REFER TO ROOM FINISH SCHEDULE 22. PROVIDE 2'-6" CLEAR. COORDINATE WITH OWNER PROVIDED EQUIPMENT 23. MITER CORNER TO PROVIDE WATERFALL EDGE






## GENERAL NOTES

- A. DO NOT SCALE DRAWINGS. B. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO CROSS-CHECK THE INTERIOR DRAWINGS WITH THE ARCHITECTURAL DRAWINGS PRIOR TO THE ORDERING / INSTALLATION OF CASEWORK. ANY DISCREPANCIES BETWEEN THE ARCHITECTURAL AND INTERIOR DRAWINGS SHALL BE BROUGHT TO THE ARCHITECTS ATTENTION FOR IMMEDIATE CLARIFICATION. C. COORDINATE THE INSTALLATION WITH OTHER TRADES AS REQUIRED TO ENSURE A NEAT AND ORDERLY INSTALLATION. NOTIFY ARCHITECT/ENGINEER OF ANY DISCREPANCIES BEFORE STARTING WORK. D. GENERAL CONTRACTOR AND SUB-CONTRACTORS SHALL CAREFULLY REVIEW THE CONSTRUCTION DOCUMENTS. INFORMATION REGARDING THE COMPLETE WORK IS DISPERSED THROUGHOUT THE DOCUMENT SET AND CANNOT BE ACCURATELY DETERMINED WITHOUT REFERENCE TO THE COMPLETE DOCUMENT SET. E. WHERE THERE MAY BE A CONFLICT IN THE SPECIFICATIONS AND/OR DRAWINGS, THEN THE MORE EXPENSIVE LABOR, MATERIALS AND EQUIPMENT SHALL BE ASSUMED TO BE REQUIRED AND SHALL BE PROVIDED BY THE GENERAL CONTRACTOR TO THE SATISFACTION OF THE TENANT. F. WHEN WORK, NOT SPECIFICALLY CALLED OUT, IS REQUIRED TO COMPLETE THE PROJECT, IT SHALL BE PROVIDED BY THE GENERAL CONTRACTOR WITH THE BEST MATERIALS AND WORKMANSHIP. G. THE PROPER RECEIPT AND UNLOADING OF ALL NEW MATERIALS AND EQUIPMENT AT THE JOBSITE IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR. SECURE AND SAFE STORAGE OF ALL MATERIALS AND EQUIPMENT WILL BE PROVIDED BY THE GENERAL CONTRACTOR. GENERAL CONTRACTOR SHALL ADVISE ARCHITECT & OWNER OF ALL DAMAGED, DEFICIENT OR OVERSHIPMENTS OF OWNER SUPPLIED MATERIALS. GENERAL CONTRACTOR SHALL COMPLETE AND SUBMIT ALL NECESSARY PAPERWORK AND ARRANGE INSPECTIONS OF DAMAGED GOODS AND RETURN AS PER CONSTRUCTION REQUIREMENTS. H. FINISHES SHALL BE SUBMITTED TO THE ARCHITECT FOR APPROVAL PRIOR TO ORDERING OR
- H. FINISHES SHALL BE SUBMITTED TO THE ARCHITECT FOR APPROVAL PRIOR TO ORDERING OR INSTALLATION, WHERE DIRECTED IN THE SPECIFICATIONS.
  I. ENSURE THAT ALL SURFACES TO RECEIVE FINISHES ARE CLEAN, TRUE AND FREE OF IRREGULARITIES. DO NOT PROCEED WITH WORK UNTIL UNSATISFACTORY CONDITIONS HAVE BEEN CORRECTED.
  J. REFER TO ELEVATIONS FOR FINISHES THAT MAY NOT BE NOTED ON THE FINISH PLAN. TRANSITION IN FLOORING SHALL BE LOCATED AT CENTER OF DOOR OR OPENING UNLESS NOTED OTHERWISE (U.N.O.).
  K. PATCH, SMOOTH AND OTHERWISE PREPARE FLOOR SLAB AS REQUIRED FOR INSTALLATION OF
- FLOORING MATERIALS. L. PROVIDE RESILIENT BASE IN ALL FINISHED FLOORING AREAS UNLESS SCHEDULED OTHERWISE. M. DO NOT INSTALL FLOORING MATERIALS OVER EXPANSION JOINTS. PROVIDE EXPANSION JOINT COVERS. N. SEE FINISH SCHEDULE, INTERIOR ELEVATIONS AND REFLECTED CEILING PLANS FOR ADDITIONAL FINISH
- INFORMATION. O. CORNER GUARDS TO BE PLACED ON ALL EXTERIOR GYPSUM BOARD CORNERS. REFER TO
- SPECIFICATION SECTION 10 26 00 FOR ADDITIONAL INFORMATION. P. PROVIDE TRANSITION AT ALL CHANGES IN FLOOR MATERIALS, UNO. Q. PATCH, SMOOTH AND OTHERWISE PREPARE FLOOR SLAB AS REQUIRED FOR INSTALLATION OF
- FLOORING MATERIALS. R. INSTALL A SOAP DISPENSER AND PAPER TOWEL DISPENSER AT EACH SINK. S. THE INTENT OF THESE ELEVATIONS IS TO SHOW LOCATIONS OF MAJOR INTERIOR ELEMENTS.
- ELEVATIONS MAY NOT SHOW ALL ITEMS IN ALL ROOMS. T. SEE TYPICAL MOUNTING HEIGHTS ON SHEET I-201. VERIFY MOUNTING HEIGHTS SHOWN FOR TOILET ACCESSORIES WILL ALLOW FOR FULL OPERATION OF UNITS. NOTIFY ARCHITECT OF ANY POSSIBLE DISCREPANCIES PRIOR TO INSTALLATION.
- U. SEE INTERIOR DETAILS FOR ADDITIONAL CASEWORK INFORMATION.
   V. CASEWORK SHALL HAVE A 4" BACKSPLASH AND/OR SIDESPLASH AND 4" TOE KICK UNLESS NOTED OTHERWISE (U.N.O.).
- W. ALL CASEWORK SHALL LOCK. LOCKS WITHIN A GIVEN ROOM SHALL BE KEYED ALIKE UNLESS OTHERWISE DIRECTED BY OWNER. COORDINATE MASTER KEYING AND OVERALL KEYING SCHEDULE
- WITH OWNER. X. WALL CABINETS 24" HIGH SHALL HAVE ONE ADJUSTABLE SHELF. WALL CABINETS 25"-36" HIGH SHALL HAVE TWO ADJUSTABLE SHELVES UNLESS INDICATED OTHERWISE ON ELEVATIONS.
- Y. BASE CABINETS SHALL HAVE ADJUSTABLE SHELVES AS INDICATED ON ELEVATIONS AND DETAILS (MINIMUM OF ONE SHELF).
- Z. CABINET SHELVING SHALL BE FULL DEPTH. DRAWER BOXES SHALL BE FULL HEIGHT. PROVIDE MAXIMUM DRAWER BOX DEPTH AVAILABLE.
- AA. INSTALL CHAIN STOPS IN ALL LOCATIONS WHERE CABINET DOOR IS ADJACENT TO A WALL OR OTHER OBSTRUCTION.
  BB. INSTALL FILLER PANELS WHERE REQUIRED. PROVIDE AT WALL JUNCTION TO ALLOW DOORS TO OPEN COMPLETELY (MINIMUM 100 DEGREES). FILLERS SHALL EXTEND THE FULL DEPTH OF CABINET TO CREATE A FLUSH SURFACE ON TOP AND/OR BOTTOM OF CASE. FILLER FINISH SHALL MATCH ADJACENT
- CASEWORK. CC. BASE AND TALL CABINETS SHALL BE 24" DEEP U.N.O. WALL CABINETS SHALL BE 14"-15" DEEP U.N.O. DD. INSTALL HEAVY-DUTY WORKSURFACE SUPPORT BRACKETS AS REQUIRED TO FULLY SUPPORT WORKSURFACE. BRACKETS SHALL BE METAL WITH WIREWAY OPENING (A&M HYBRID BRACKETS OR

EQUAL). COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE. EE. INSTALL GROMMETS IN WORKSURFACES FOR ACCESS TO ELECTRIC AND DATA OUTLETS. COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE. FF. ALL FURNITURE AND EQUIPMENT SHALL BE OWNER PROVIDED U.N.O. SHOWN IN PLAN FOR REFERENCE.


## LEGEND



SV-1 SV-2

PLAN KEYED NOTES:

INDICATED BY




KEY PLAN SCALE: NTS

-

VIVARIUM

<section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header>						
<section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header>						
W. DANIEL         BICKERSTAFF, II         12608         W. DANIEL         BICKERSTAFF, II         Lickerstaff, II License No. 12608         Expiration Date: December 31, 2023						
PRE-BID QUESTION RI PERMIT ISSUANCE ISSUED	ESPONSES	WDB, II WDB, II BY	11.04.2022 08.26.2022 DATE			
CLARA E. WESTROPP ELEMENTARY SCHOOL						
New MetroHealth ODH SBHC Health Care Expansion Program						
MEDICAL CENTER 2500 METROHEALTH DR. CLEVELAND, OH 44109						
Andrese       Date         Hollie Dellisanti EDUCATOR, Exec. Dir.       Date         Architectural Projects, Capital Projects       Date         Consultant Project #       Drawn by:         DB       Checked by:         WDB, II       FINISHES AND         EQUIPMENT PLANS         Scale:       Sheet:						
Date: 11.04.2022		A	4.0			



	R	OOM FINIS	H SCHEDU	LE		
	FLOOR		WALL FINISH- selection by Owner			
	FINISH	BASE	NORTH	SOUTH	EAST	WEST
	SV-2	RB-1				
	SV-2	RB-1				
	SV-1	RB-1				
N	SV-2	RB-1				
	SV-2	RB-1				
	SV-2	RB-1				
1	SV-1	RB-1				
	SV-1	RB-1				
	SV-2	RB-1				
DS	SV-2	RB-1				
	SV-2	RB-2				
	SV-2	RB-1				

# SOLID SURFACE COUNTERTOP

## GENERAL NOTES

- A. ALL OUTSIDE CORNERS OF GYPSUM BOARD WALLS SHALL RECEIVE CORNER GUARDS. INSTALL CORNER GUARDS AT TOP OF BASE.
- B. PROVIDE TRANSITIONS AT ALL CHANGES IN FLOORING FINISH, UNO. C. FLOOR MATERIALS AND/OR COLOR CHANGES BETWEEN ROOMS OR SPACES SHALL TRANSITION AT CENTER OF DOOR OR OPENING UNLESS NOTED OTHERWISE (U.N.O.). D. ALL EXPOSED CONDUIT, DUCTWORK, ACCESS PANELS, STRUCTURAL STEEL, ETC. SHALL BE PAINTED TO MATCH WALL OR CEILING U.N.O.
- E. INTERIOR HOLLOW METAL WINDOW FRAMES SHALL BE PAINTED TO MATCH DOOR FRAMES U.N.O. F. FINISH SCHEDULE CALLS OUT PAINT COLOR ONLY. SEE SPECIFICATIONS FOR PAINT TYPE AND SHEEN. G. SEE INTERIOR PLANS FOR ADDITIONAL ACCENT PAINT COLORS AND LOCATIONS. H. SEE INTERIOR PLANS FOR FLOOR PATTERNS AND ACCENT PAINT LOCATIONS.
- I. SEE REFLECTED CEILING PLANS FOR SOFFIT PAINT COLORS. J. PAINT INTERIOR DOOR FRAMES AND HOLLOW METAL DOORS P-X U.N.O.
- K. DO NOT INSTALL FLOORING MATERIALS OVER EXPANSION JOINTS. PROVIDE EXPANSION JOINT COVERS. L. ALL CASEWORK SHALL LOCK. LOCKS WITHIN A GIVEN ROOM SHALL BE KEYED ALIKE UNLESS OTHERWISE DIRECTED BY OWNER. COORDINATE MASTER KEYING AND OVERALL KEYING SCHEDULE WITH OWNER.
- M. CASEWORK SHALL HAVE A 4" BACKSPLASH AND/OR SIDESPLASH AND 4" TOE KICK UNLESS NOTED OTHERWISE (U.N.O.). N. WALL CABINETS 24" HIGH SHALL HAVE ONE ADJUSTABLE SHELF. WALL CABINETS 25"-36" HIGH SHALL
- HAVE TWO ADJUSTABLE SHELVES UNLESS INDICATED OTHERWISE ON ELEVATIONS. O. BASE CABINETS SHALL HAVE ADJUSTABLE SHELVES AS INDICATED ON ELEVATIONS AND DETAILS
- (MINIMUM OF ONE SHELF). P. CABINET SHELVING SHALL BE FULL DEPTH. DRAWER BOXES SHALL BE FULL HEIGHT. PROVIDE
- MAXIMUM DRAWER BOX DEPTH AVAILABLE. Q. INSTALL CHAIN STOPS IN ALL LOCATIONS WHERE CABINET DOOR IS ADJACENT TO A WALL OR OTHER
- OBSTRUCTION. R. INSTALL FILLER PANELS WHERE REQUIRED. PROVIDE AT WALL JUNCTION TO ALLOW DOORS TO OPEN COMPLETELY (MINIMUM 100 DEGREES). FILLERS SHALL EXTEND THE FULL DEPTH OF CABINET TO CREATE A FLUSH SURFACE ON TOP AND/OR BOTTOM OF CASE. FILLER FINISH SHALL MATCH ADJACENT CASEWORK.
- S. BASE AND TALL CABINETS SHALL BE 24" DEEP U.N.O. WALL CABINETS SHALL BE 14"-15" DEEP U.N.O. T. INSTALL HEAVY-DUTY WORKSURFACE SUPPORT BRACKETS AS REQUIRED TO FULLY SUPPORT WORKSURFACE. BRACKETS SHALL BE METAL WITH WIREWAY OPENING (A&M HARDWARE HYBRID BRACKETS OR EQUAL). COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.
- U. INSTALL GROMMETS IN WORKSURFACES FOR ACCESS TO ELECTRIC AND DATA OUTLETS. COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE. V. INSTALL A SOAP DISPENSER AND PAPER TOWEL DISPENSER AT EACH SINK.
- W. THE INTENT OF THESE ELEVATIONS IS TO SHOW LOCATIONS OF MAJOR INTERIOR ELEMENTS. ELEVATIONS MAY NOT SHOW ALL ITEMS IN ALL ROOMS. X. ALL FURNITURE AND EQUIPMENT SHALL BE OWNER PROVIDED U.N.O.

## **REFERENCED KEYNOTES**

09 65 13.A	RESILIENT BASE
12 32 16.B1A	ACCESSIBLE SINK BASE
12 32 16.B3	DOOR/DRAWER BASE
12 32 16.B4	DRAWER BASE
12 32 16.F	FILLER PANEL
12 32 16.W1	WALL CABINET
12 36 61.16.A	SOLID SURFACE MATERIAL COUNTERTOP

06 40 23 INTERIOR ARCHITECTURAL WOODWORK

- 08 87 00 ARCHITECTURAL WINDOW FILMS
- 09 51 13 ACOUSTICAL PANEL CEILINGS 09 65 13 RESILIENT BASE AND ACCESSORIES
- 09 65 16 RESILIENT SHEET FLOORING 09 91 23 INTERIOR PAINTING
- 10 26 00WALL AND DOOR PROTECTION10 28 00TOILET, BATH, AND LAUNDRY ACCESSORIES
- 12 32 16 MANUFACTURED PLASTIC-LAMINATE CLAD CASEWORK 12 36 61.16 SOLID SURFACING COUNTERTOPS

## **ABBREVIATIONS**

- P PAINT PC POLISHED CONCRETE PL PLASTIC LAMINATE RB RESILIENT BASE SS SOLID SURFACE
- SV SHEET VINYL
- 10 28 00 TOIL FT ROOM ACCESSORIES
- CH-1 COAT HOOK GB-1 GRAB BAR, 36" GB-2 GRAB BAR, 42"
- GB-2 GB-3 GRAB BAR, 18" MIRROR 24"x60" PAPER TOWEL DISPENSER M-1
- PT-1 SANITARY UNIT DISPOSAL SUD-1 TOILET TISSUE DISPENSER

## PLAN KEYNOTES

- . 1/2 PLYWOOD SUBSTRATE 1/2" MILLWORK REVEAL, STAINLESS STEEL. MFG: FRY REGLET, OR EQUAL
- 1/2" RADIUS 1/2" SOLID SURFACE COUNTER ON PLYWOOD SUBSTRATE
- 4" HIGH (U.N.O.) AND 1/2" THICK BACKSPLASH . ADJUSTABLE SHELF . BLOCKING AS REQUIRED
- 3. CABLE TRAY CHASE
- . CEILING. REFER TO REFLECTED CEILING PLAN FOR ADDITIONAL INFORMATION DRAWERS SIDES SHALL BE FULL HEIGHT WITH INTEGRAL FILE RAILS
- 11. DRAWERS SIDES SHALL BE FULL HEIGHT 12. GROMMET
- 13. METAL SUPPORT BRACKET. MFG: A&M HARDWARE, HYBRID WORKSTATION BRACKET OR EQUAL 14. PLAM ENCLOSURE ABOVE WALL CABINET. FACE OF ENCLOSURE SHALL BE FLUSH WITH
- FRONT AND SIDE OF WALL CABINET AND EXTEND TO UNDERSIDE OF CEILING. PLAM ON 3/4" PLYWOOD, FASTENED TO STUD FRAME WITH CONCEALED FASTENERS
- 15. PROVIDE PROTECTION AT KNEE CLEARANCE, SINK SHALL NOT BE EXPOSED 16. PROVIDE STRUCTURAL SUPPORT AS REQUIRED 17. REMOVABLE ACCESS PANEL
- 18. RESILIENT BASE 19. TACKBOARD
- 20. WORKSURFACE
- 21. FOR WALL FINISH, REFER TO ROOM FINISH SCHEDULE 22. PROVIDE 2'-6" CLEAR. COORDINATE WITH OWNER PROVIDED EQUIPMENT 23. MITER CORNER TO PROVIDE WATERFALL EDGE

<section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header>					
<section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header>					
VOFUU <td< td=""></td<>					
PRE-BID QUESTION RI PERMIT ISSUANCE	ESPONSES	WDB, II WDB, II	11.04.2022 08.26.2022		
19101 Puritas Avenue Cleveland, OH 44135 <b>Medical Center</b> 2500 METROHEALTH DR. CLEVELAND, OH 44109					
Hollie Dellisanti EDUCATOR, Exec. Dir. Architectural Projects, Capital Projects Date Consultant Project # Drawn by: DB Checked by: WDB, II					
INTERIOR ELEVATIONS AND SCHEDULES					
Date: 11.04.2022			5.0		